- **Exceptional water savings**: 90%
- **Hygiene**: no manual contact, anti-bacterial duty flush, spout with smooth interior and low water volume, reduced-stagnation solenoid valves
- **Simplified installation and maintenance**: LED diagnostic aids, set manually or using application via Bluetooth®

BINOPTIC 2

Wall-mounted electronic tap/mixer

NEW



Pair it with

NEW




Soap dispenser
(see page 77)

- **230/6V mains supply.**
- **Reduced-stagnation solenoid valve and electronic unit are integrated** into the body of the tap/mixer.
- **Flow rate pre-set at 3 lpm** at 3 bar, can be adjusted from 1.4 - 6 lpm.
- **Scale-resistant aerator.**
- **Adjustable duty flush** (pre-set flush ~60 seconds every 24 hours after last use).
- **Wall-mounted stainless steel tap/mixer.**
- Sensor at the end of the spout optimises presence detection.
- Anti-blocking security.
- **Spout with smooth interior** and low water volume (reduces bacterial development).
- Side temperature control with adjustable maximum temperature limiter on mixers.
- Manually set presence detection range, duty flush and launch thermal shocks *(see page 29)*.
- **Bluetooth® version is available:** advanced settings and operational data download with the **DELABIE Connect application** *(see page 28)*.
- Suitable for people with reduced mobility.
- 30-year warranty.


Product currently under development.

	½"	Ø15mm for comp. fittings (UK/Ireland)
BINOPTIC 2 wall-mounted tap/mixer		
Satin finish		
Kit 1: Nanny joint for recessed water inlet Kit 2: Mixer L. 240mm with stopcocks	**484012 + 484000**	-
Tap L. 220mm without stopcock - Recessed	**384100**	-
Tap L. 140mm with stopcock - For thin panels	**383000**	-
Chrome-plated finish		
Kit 1: Nanny joint for recessed water inlet Kit 2: Mixer L. 240mm with stopcocks	**484012 + 484010**	-
Kit 1: Nanny joint for recessed water inlet Kit 2: Mixer Bluetooth® Connect series L. 240mm with stopcocks	**484012 + 484010E**	-
Mixer L. 220mm with stopcocks For cross wall installation	**482010**	**48201015**
Tap L. 220mm without stopcock - Recessed	**384110**	-
Tap Bluetooth® Connect series L. 220mm - without stopcock - Recessed	**384110E**	-
Tap L. 140mm with stopcock - For thin panels	**383010**	-
Tap L. 140mm with stopcock For cross wall installation	**381010**	**38101015**
Tap L. 220mm with stopcock For cross wall installation	**382010**	**38201015**
Matte black chrome finish		
Mixer L. 220mm with stopcocks For cross wall installation	**482030**	**48203015**
Tap L. 220mm without stopcock - Recessed	**384130**	-
Stopcocks		
Stopcock MF⅜" L. 45mm - 1 unit		**825212**
Stopcocks MF⅜" L. 45mm - 2 units		**825212.2P**

We recommend installing a TMV for taps *(see page 143)*
For cross wall taps and mixers without stopcocks, please visit our website delabie.com



38101015



484012 + 484000



Long lever