SECURITHERM Securitouch shower mixer

Sequential thermostatic mixer, with no non-return valves





- **Sequential:** opens and closes with cold water *(see page 112).*
- **No risk of cross flow between hot and cold water.**
  No non-return valves on the inlets.
- **Anti-scalding failsafe:** automatic shut-off if cold water supply fails.
- **Prevents cold showers:** automatic shut-off if hot water supply fails.
- **Securitouch thermal insulation prevents burns.**
- Scale-resistant **sequential thermostatic cartridge.**
- Temperature control: cold water up to 39°C.
- Temperature limiter set at 39°C.
- For ref.s H963015 and H964015: tested without water to comply with NHS requirements (UK). No pre-set temperature.
- Thermal shocks are possible.
- **Body with smooth interior and low water volume** (reduces bacterial development).
- Flow rate regulated at 9 lpm.
- Hygiene control lever L. 100mm.
- Top or bottom outlet options.
- Supplied with 2 offset STOP/CHECK connectors M½" M¾" (ref. 855755.2P), 2 in-line STOP/CHECK connectors M½" M¾" (ref. 855755UK.2P) or 2 offset standard connectors M½" M¾" (ref. 856794.2P) *(see page 140).*
- Suitable for people with reduced mobility.
- 30-year warranty.



Smooth interior = very little biofilm
Thermal insulation on HW side
No non-return valves

SECURITHERM Securitouch sequential thermostatic shower mixer	
Bottom outlet	
Offset STOP/CHECK connectors	**H9630**
In-line STOP/CHECK connectors - tested without water (NHS compliant)	**H963015**
Offset standard connectors	**H9630S**
Without connectors for renovation	**9630**
Top outlet	
Offset STOP/CHECK connectors	**H9640**
In-line STOP/CHECK connectors - tested without water (NHS compliant)	**H964015**
Offset standard connectors	**H9640S**

Options: hydrotherapy accessories *(see pages 137 - 139),* BIOFIL shower head filters *(see page 138),* auto-draining device *(see page 140),* floor traps *(see page 143)*







H9630



H964015