
TEMPOMATIC 4

Wall-mounted electronic mixer and tap, mains supply or battery-operated




- **230/6V mains supply** or **integrated CR123 6V Lithium batteries.**
- **Reduced-stagnation solenoid valve and electronic unit integrated** into the body of the mixer or tap.
- **Scale-resistant flow straightener.**
- **Duty flush** (~60 seconds every 24 hours after last use).
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.
- Presence detection sensor at the end of the spout optimises detection.
- Cap fixed in place by 2 concealed screws.
- Compact nanny joint (for mixers with recessed water inlets).
- Stopcocks.
- Anti-blocking security.
- Side temperature control with adjustable maximum temperature limiter on mixers.
- Recommended installation height: 300mm above the basin surface.
- Suitable for people with reduced mobility.
- 30-year warranty.




Standard lever

TEMPOMATIC MIX 4 wall-mounted mixer	
Recessed mains supply	
Kit 1: Nanny joint for recessed water inlet Kit 2: Wall-mounted mixer L. 160mm	**484012** **+ 493400**
Kit 1: Nanny joint for recessed water inlet Kit 2: Wall-mounted mixer L. 220mm	**484012** **+ 493500**
Cross wall L. 190mm	**493510**
Battery-operated	
Kit 1: Nanny joint for recessed water inlet Kit 2: Wall-mounted mixer L. 160mm	**484612** **+ 493406**
Kit 1: Nanny joint for recessed water inlet Kit 2: Wall-mounted mixer L. 220mm	**484612** **+ 493506**
Cross wall L. 190mm	**493516**
TEMPOMATIC 4 wall-mounted tap	
Recessed mains supply	
Wall-mounted L. 130mm (recessed water inlet)	**443400**
Wall-mounted L. 190mm (recessed water inlet)	**443500**
Cross wall L. 130mm	**443410**
Cross wall L. 190mm	**443510**
Battery-operated	
Wall-mounted L. 130mm (recessed water inlet)	**443406**
Wall-mounted L. 190mm (recessed water inlet)	**443506**
Cross wall L. 130mm	**443416**
Cross wall L. 190mm	**443516**
Panel-mounted ≤ 24mm or solid walls L. 130mm	**443426**
Panel-mounted ≤ 24mm or solid walls L. 190mm	**443526**
L. 130mm for refurbishment	**443436**
L. 190mm for refurbishment	**443536**


We recommend installing a TMV for taps *(see page 103)*




484012 + 493400



493516



443410



443506