
- **Exceptional water savings**: 90%
- **Hygiene**: no manual contact, reduced-stagnation solenoid valves, anti-bacterial duty flush
- **Easy to install**: solenoid valve and electronics integrated into the body of the tap
- **Specifically designed for public and commercial places**: batteries last 3 - 6 years, metal body, 30-year warranty

TEMPOMATIC 5
Deck-mounted electronic basin tap/mixer



- **230/6V mains supply** or **integrated CR123 6V Lithium batteries.**
- **Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.**
- **Flow rate pre-set at 3 lpm** at 3 bar, can be adjusted from 1.4 - 6 lpm.
- **Scale-resistant flow straightener.**
- **Duty flush.**
- Active, infrared presence detection, sensor at the end of the spout optimises detection.
- Chrome-plated metal body.
- PEX flexibles with filters and non-return valves.
- Fixing reinforced by 2 stainless steel rods.
- Anti-blocking security.
- Side temperature control with adjustable maximum temperature limiter on mixers.
- Suitable for people with reduced mobility.
- 30-year warranty.



499106



Standard lever


	F3/8" with stopcock	F3/8" without stopcock	Ø15mm for comp. fittings (UK/Ireland)
TEMPOMATIC MIX 5 mixer			
Mains supply - recessed unit	**499000**	**499100**	**49900015**
Mains supply - plug-in	**499001**	**499101**	**-**
Battery-operated	**499006**	**499106**	**49900615**
TEMPOMATIC 5 tap			
Mains supply - recessed unit	**449000**	**449100**	**44900015**
Mains supply - plug-in	**449001**	**449101**	**-**
Battery-operated	**449006**	**449106**	**44900615**

We recommend installing a TMV for taps *(see page 143)*


TEMPOMATIC 5
Wall-mounted electronic basin tap/mixer




- **230/6V mains supply** or **integrated CR123 6V Lithium batteries.**
- **Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer.**
- **Flow rate pre-set at 3 lpm** at 3 bar, can be adjusted from 1.4 - 6 lpm.
- **Scale-resistant flow straightener.**
- **Duty flush.**
- Active, infrared presence detection, sensor at the end of the spout optimises detection.
- Chrome-plated metal body.
- Stopcocks.
- Anti-blocking security.
- Side temperature control with adjustable maximum temperature limiter on mixers.
- Suitable for people with reduced mobility.
- 30-year warranty.



449410



499416



Standard lever

Product currently under development.

TEMPOMATIC MIX 5 wall-mounted mixer L. 180mm for cross wall installation	
Mains supply	**499410**
Battery-operated	**499416**
M3/8" connection Ø 15mm for compression fittings (2 pieces)	**803815.2P**
TEMPOMATIC 5 wall-mounted tap L. 150mm for cross wall installation	
Mains supply	**449410**
Battery-operated	**449416**
TEMPOMATIC 5 wall-mounted tap L. 150mm for recessed water inlet	
Battery-operated, without stopcock	**449406**
Reinforced exposed union Ø 50mm	**841215**

We recommend installing a TMV for taps *(see page 143)*